

# ENC-8211S PCIe x8 Network Module with Dual 10000M Optical Fiber Ports



## Features

- Server-grade network adapter
- Intel® 82599ES 10000M network chip
- 2 x 10Gb optical fiber port
- PCIe 2.0 supported, the physical sequence of each network port provides up to 128 channels for send & receive, supporting Auto-negotiation and IPSec



**Parhelia B.V.**

[info@parhelia-bv.eu](mailto:info@parhelia-bv.eu)

[www.parhelia-bv.com](http://www.parhelia-bv.com)

+31(0)10 741 00 28

<b>Specifications</b>	Short PCIe card
<b>Interface Structure</b>	Brackets, including long and short brackets
<b>Network Port</b>	2 x SFP + 10Gb optical fiber network port
<b>Ethernet</b>	Intel® 82599ES 10000M network chip
<b>Operating System</b>	Windows Sever 2008, LINUX Temperature: 0°C~55°C;
<b>Operating Environment</b>	Humidity: 5%~95%, non-condensing; Temperature: -20°C~80°C;
<b>Storage Environment</b>	Humidity: 5%~95%, non-condensing; Limits of radio disturbance are compliant with GB9254-1998 class A;
<b>EMC</b>	Immunity to disturbance is compliant with the limits of GB/T 17618.5-2008
<b>Dimensions</b>	171.9mm (L) x 69mm (W) x 18mm (H)