



RRT-35SCSI-SN-R-CFast 3.5" SCSI 50-Pin Narrow with Removable CFast

THE 3.5" 50-PIN SCSI NARROW WITH REMOVABLE CFAST uses a proprietary FPGA-based design that provides a long term solution for replacement of obsolete SCSI hard drives, SCSI SSD, SCSI Magneto Optical (MO), SCSI tape drive, SCSI Floppy drive, SCSI CD, DVD, DVD-RAM, and PC card drives.

The design provides a transparent interface from the SCSI bus to a COTS CFast card. Custom firmware provided for SCSI systems that require specific SCSI command responses, capacities, or sector sizes. A built-in debug monitor can be used to diagnose issues and update firmware.

Emulations for:

- SCSI fixed drive to replace hard drive or SSD
- SCSI Removable drive
- SCSI Magneto Optical (MO)
- SCSI DAT Tape
- SCSI Floppy,
- SCSI CD, DVD
- SCSI PC Card

- Drop in replacement for obsolete SCSI drives
- 50-pin Narrow 8-bit Single Ended (SE) Ultra SCSI interface
- Hot-swap Removable CFast
- Built-in debug monitor for diagnostics and updates to firmware
- Standard 3.5" form factor
- Transfer rates up to 20 MB/s
- Capacities up to 1TB
- Extended temperature option
- SCSI termination can be enabled within unit
- CFast with write protect switch available
- ROHS Compliant
- SCSI ID selection 0 - 7
- US-Based Engineering and Manufacturing
- In-house Technical Support



Parhelia B.V.
www.parheliabv.com
+31(0)10 741 00 28

Ordering Information

3.5" SCSI with Removable CFast

RRT-35SCSI-SN-R-CFast- **FLOPPY** - **UR** - **X** - **SECTORSIZE1024**

Options May be left blank

Emulation

Floppy	Floppy Drive
MO	Magneto Optical
DAT	Tape Drive
CD	CD Drive
DVD	DVD Drive

Conformal Coating

UR	Polyurethane
AR	Acrylic

Extended Temperature Range

X	-40°C to 85°C
---	---------------

Sector Size

(512 byte default sector size)
256, 768, 1024, or any value

ORDER EXAMPLES

RRT-35SCSI-SN-R-CFast-UR-X-SECTORSIZE256
RRT-35SCSI-SN-R-CFast-FLOPPY

CFast Card

RRT-CFAST- **SLC** - **8GB** - **X** - **WP**

Requirements

NAND Flash Type

SLC	Single Level Cell
MLC	Multi Level Cell
TLC	Tri Level Cell (3D)

Capacity

4GB - 64GB	SLC
8GB - 512GB	MLC
32GB - 1TB	TLC

Options May be left blank

Write Protect

WP	Write Protect
----	---------------

Extended Temperature Range

X	-40°C to 85°C
---	---------------

ORDER EXAMPLES

RRT-CFAST-MLC-512GB
RRT-CFAST-SLC-8GB-X-WP



Parhelia B.V.

www.parheliabv.com

+31(0)10 741 00 28

Product Specifications

3.5" SCSI 50-PIN NARROW WITH REMOVABLE CFAST

PERFORMANCE

INTERFACE	Narrow 8-bit Single Ended (SE) Ultra SCSI, SCSI2, SCSI1
SUSTAINED THROUGHPUT READ/WRITE	19 MB/s
SECTOR SIZE	512 bytes or custom sector size

RELIABILITY

MTBF - DRIVE CARRIER ¹	3 million hours
-----------------------------------	-----------------

POWER

VOLTAGE	+5V +/- 5%
WATTS (IDLE)	3 W
WATTS (ACTIVE)	4 W max

ENVIRONMENTAL

OPERATING TEMP.	0 °C to 70 °C
EXTENDED OPERATING TEMP.	-40°C to 85°C
STORAGE TEMP.	-40°C to 85°C
ALTITUDE	80,000 ft. (24,000 meters)
RELATIVE HUMIDITY	5% to 95% non-condensing
SHOCK	50g 11 millisecond
VIBRATION ⁴	12.0 Grms 20 Hz to 2000 Hz

PHYSICAL

FORM FACTOR	3.5" drive
WEIGHT	10.85 oz. max (307.6g)
DIMENSIONS	4" (101.6mm) X 6.6" (167.6mm) with retainer, 6" (152.4mm) (without retainer) X 1" (25.4mm)

NOTES

(1) Telcordia SR-322, Issue 3, operating temp (40C), electrical stress (50%), environmental factor (1.0).



Parhelia B.V.
www.parheliabv.com
☎ +31(0)10 741 00 28



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2023 Red Rock Technologies, Inc.
All rights reserved. (Rev. 20230105a)