


P210-06 / P210-07 ME P2 Adapters with SATA Interface

THE VME P2 ADAPTERS WITH SATA INTERFACE are I/O adapters for use with VME 3-row or VME64 5-row backplanes. Routes SATA signals from 1, 2 or 3 SATA devices on Red Rock's VME boards to standard SATA connectors on the adapter. Plugs into the back of the VME backplane and makes connections to signals on rows A and C and to ground pins of rows Z and B of the 5-row P2 connector. Used to make connections to SATA controller on the systems' SBC.





- Can be used on any VME system where rows A & C of P2 connectors on backplane are not used
- Low cost way to route signals from back of backplane to the single-board computer
- Supports high performance SATA3 transfer rates, backwards compatible with SATA1 and SATA2
- No additional hardware required



Parhelia B.V. www.parheliabv.com ①+31(0)10 741 00 28









Ordering Information

SATA P2 Adapter P2I0- 06 Backplane 06 3-Row VME DIN connector 07 5-Row VME64 DIN connector ORDER EXAMPLES P2I0-06 P2I0-07

Product Specifications

VME P2 SATA ADAPTERS

RELIABILITY	
MTBF - DRIVE CARRIER	3 million hours
ENVIRONMENTAL	
OPERATING TEMP.	-40°C to 85°C
STORAGE TEMP.	-50°C to 95°C
PHYSICAL	
DIMENSIONS	3.93" x 1.88" (9.98 cm x 4.78 cm)
WEIGHT	2 oz. max (57g)



Parhelia B.V. www.parheliabv.com ①+31(0)10 741 00 28



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc. © Copyright 2022 Red Rock Technologies, Inc. All rights reserved. (Rev. 20220603a)







